

**MATERIAL SAFETY DATA SHEET**  
**Complies with OSHA's Hazard Communication**  
**Standard 29 CFR 1910.1200**

Identity (As listed on label): 25 Year Caulk  
UPC: 22566, 22574, 97139  
HMIS: H:0 F:0 R:0 P:None

---

**SECTION I**

Macklanburg-Duncan P.O. BOX 25188 4041 North Santa Fe OKC, OK 73118  
24-Hour Number (405) 528-4411  
Emergency Number (800) 424-9300 (Chemtrec)  
Date Prepared: September 22, 1995  
Replaces: August 15, 1994

---

**SECTION II Hazardous Ingredients / Identity Information**

Component	ACGIH TLV/OSHA PEL	% Less Than by Weight	CAS NUMBER
This product contains toxic chemicals, marked by an asterisk (*), subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).			
mineral spirits	200 ppm/500 ppm	2	64742-47-8
*ethylene glycol	50 ppm/NE	2	107-21-1

---

**SECTION III Physical / Chemical Characteristics**

Boiling Point (degrees F): >300 F (mineral spirits)  
Vapor Pressure (mm Hg): <11 mm Hg (mineral spirits)  
Vapor Density (Air = 1): heavier  
Specific Gravity (Water = 1): 1.6  
% Solids: 82%  
Evaporation Rate (Butyl Acetate = 1): slower than  
Solubility in Water: soluble  
Appearance and Odor: white or pigmented semi-solid with slight odor

---

**SECTION IV Fire and Explosion Hazards**

Flash Point (Method Used) (degrees F): >200 degrees F, TOC  
Flammable Limits LEL: 1 UEL: 6 (mineral spirits)  
Extinguishing Media: Carbon dioxide, foam, dry chemical, water  
Special Fire Fighting Procedures: Self-contained breathing apparatus in positive pressure mode and full protective gear should be worn.  
Unusual Fire and Explosion Hazards: Irritating or toxic gases and aerosols may be produced during burning.

---

**SECTION V Reactivity Data**

Stability: stable  
Conditions to avoid: none  
Incompatibility (Materials to Avoid): none  
Hazardous Decomposition or Byproducts: Carbon monoxide, carbon dioxide  
Hazardous Polymerization Risk: none  
Conditions to Avoid: none

---

**SECTION VI Health Hazard Data**

Route(s) of Entry: Inhalation, skin, ingestion.  
Emergency First Aid Procedures: If comes in contact with eyes flush with water for 15 minutes and contact physician.  
Do not ingest. If swallowed, do not induce vomiting administer water, contact physician.  
Symptoms of Exposure: Dizziness, abdominal discomfort, CNS depression, headache, conjunctivitis, nausea, mucous membrane irritation.

25 Year Caulk, Page 2 of 2

Medical Conditions Aggravated by Exposure: none  
Carcinogenicity: Not known to be carcinogenic.

---

**SECTION VII                      Precautions for Safe Handling and Use**

---

Steps To Be Taken In Case Material is Spilled or Released: Scrape into containers and dispose of in accordance with local, state, and federal regulations.

Waste Disposal Method: Dispose of material in accordance with local, state, and federal regulations.

Handling and Storage Precautions: Do not store near heat sources, sparks, or flame. Store between 40 degrees and 120 degrees F. Do not freeze.

Other Precautions: Do not ingest. Keep away from children.

**NOT FOR UNDERWATER USE.**

---

**SECTION VIII                      Control Measures**

---

Respiratory Protection: adequate ventilation-mechanical exhaust recommended

Protective Gloves: not necessary

Eye Protection: normal precaution

Hygienic Practices: Wash skin and hands after use.